

SUBMITTAL SHEET

MALLEABLE IRON 90 DEG ANGLE LIQUIDTIGHT CONNECTORS

DESCRIPTION:

Orbit Industries' malleable iron 90° angle liquid tight connectors are used on flexible metallic liquid tight conduits and Type B flexible non-metallic liquid tight conduits to positively bond conduits to boxes or enclosures in both wet and damp locations. In addition, when connectors are terminated in threadless openings, the included sealing washers provide liquid tight seals. The heavy duty locknuts included with every Orbit liquid tight connector ensures the continuity of the grounding. In damp locations, the connectors are also of excellent corrosion protection with zinc electroplated. The trade size varies from 3/8" to 4".



FEATURES:

- Malleable Iron
- Electroplated Zinc
- Insulated color may vary
- NPT Male Threads
- Suitable for use in hazardous locations: Class I, Division 2; Class II, Divisions 1 & 2; and Class III, Divisions 1 & 2 per NEC

CERTIFICATION:

UL file E310658, Conforms to UL 514B



CONFIGURATION DATA:

Part No.	UPC	Trade Size	Std.Pkg.	Master Ctn
MLT90-38	8-35243-03121-0	3/8"	25	150
MLT90-50	8-35243-03122-7	1/2"	25	150
MLT90-75	8-35243-03123-4	3/4"	10	100
MLT90-100	8-35243-03124-1	1"	5	50
MLT90-125	8-35243-03125-8	1-1/4"	5	40
MLT90-150	8-35243-03126-5	1-1/2"	4	20
MLT90-200	8-35243-03127-2	2"	1	15
MLT90-250	8-35243-05334-2	2-1/2"	-	1
MLT90-300	8-35243-05335-9	3"	-	1
MLT90-350	8-35243-05336-6	3-1/2"	-	1
MLT90-400	8-35243-05337-3	4"	-	1

