

Project:

Type:

Prepared By:

Date:



Features and Benefits

Replaces 13W CFL Lamps

Plug and Play on existing magnetic CFL ballasts or can be wired directly to line voltage without need for an external driver or ballast

Compatible with Gx23 base installations

50,000 hour Lifespan

Environmentally friendly, no mercury used

UL Classified

Rated for use in enclosed and open fixtures in dry or damp locations

5 Year No Compromise Warranty

Technical Specifications		
<div><div>Performance</div><div>Product Type:</div><div>Compact</div><div>Input Wattage:</div><div>5.5W</div><div>Lumens:</div><div>600lm</div><div>Efficacy:</div><div>109.1lm/W</div><div>L70 Lifespan:</div><div>50,000-Hour LED lifespan based on IES LM-70 results</div><div>Wattage Equivalency:</div><div>11W CFL</div><div>LED Characteristics</div><div>Color Accuracy (CRI):</div><div>80 CRI</div><div>Beam Angle:</div><div>120°</div></div>	<div><div>Color Temperature:</div><div>5000K</div><div>Construction</div><div>Material:</div><div>Polycarbonate</div><div>Bulb Shape:</div><div>PLS-Horizontal</div><div>Installation</div><div>Base Type:</div><div>Gx23</div><div>Electrical</div><div>Power Factor:</div><div>>0.9</div><div>Input Voltage:</div><div>120-277V</div><div>Operating Temperature:</div><div>-20°C to 45°C (-4°F to 113°F)</div><div>Compliance</div><div>Enclosed Fixtures:</div><div>Suitable for use in enclosed fixtures</div></div>	<div><div>UL Listed:</div><div>Suitable for damp locations</div><div>UL Classified:</div><div>Yes</div><div>Certification Model Number:</div><div>T10369(PLS-5.2-H-850-HYB)</div></div>

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	7.2	5.4	3
PALLET	0	0	0	0

[illegible]