

SPECIFICATION & FEATURES

UNIVERSAL FLAT DEVICE COVERS

FEATURES:

- Device Inserts
- Clean installation with no break-off parts
- Heavy-Duty Die-Cast Metal with polycarbonate Inserts
- Pad lockable design
- Pre-installed Adhesive Gasket
- Meets NEC Article 406.9 (A) for damp and wet locations

CERTIFICATION:



Wet Location



1C-U

5 in 1



2C-U

16 in 1




3C-U

64 in 1

CONFIGURATION DATA:

Part No.			Description	Std.Pkg.
Gray	Bronze	White		
1C-U	1C-U-BR	1C-U-W	1-Gang	25
2C-U	2C-U-BR	2C-U-W	2-Gang	12
3C-U	-	-	3-Gang	10



1C-U Includes:

- 1 x Toggle Switch
- 1 x Duplex Receptacle
- 1 x GFCI/Decorative
- 1 x 1-3/8"
- 1 x 1-9/16"~1-5/8"

2C-U Includes:

- 2 x Toggle Switch
- 2 x Duplex Receptacle
- 2 x GFCI/Decorative
- 2 x 1-3/8"

3C-U Includes:

- 3 x Toggle Switch
- 3 x Duplex Receptacle
- 3 x GFCI/Decorative
- 3 x 1-3/8"

Easy-to-Assemble Building-Block
Style Adapters Accommodate
a Wide Range of Wiring Devices

